

# BRUSH CUTTERS



## BC2321H-RS



### Specifications

#### BC2321H-RS Specifications

|   |                         |
|---|-------------------------|
| Dimensions (LxWxH)                                    | 1780x730x465 mm         |
| Dry Weight  | 6.1kg                   |
| Engine  | CER230 (22.5cc)         |
| Output  | 0.77kw                  |
| Fuel tank   | 0.45L                   |
| Handle  | Double                  |
| Recoil Starting System                                | Reverse Start 2         |
| Drive Shaft   | Solid steel $\phi$ 7mm  |
| Accessory (Blade)                                     | 4 teeth (230)           |
| Accessory (Nylon head)                                | Semi-Auto L(4)          |
| Harness   | Single                  |
| Vibration Level* <sup>1</sup>                         |                         |
| Left Handle(Blade/Nylon)                              | 4.2/5.4m/s <sup>2</sup> |
| Right Handle(Blade/Nylon Head)                        | 5.3/5.6m/s <sup>2</sup> |
| Sound Pressure Level (Blade/Nylon Head)* <sup>2</sup> | 91.5/93.5dB(A)          |

\*<sup>1</sup> Vibration Level on the handles measured according to ISO 22867 (m/s<sup>2</sup>)

\*<sup>2</sup> Sound Pressure Level measured according to ISO 22868

Where ever you are, What ever the job.  
Make it a Maruyama Brush cutter.



#### Treaded Clutch Shaft

The solid steel inner drive-shaft is threaded at the clutch end, which eliminates vibration.



#### Ergonomic Design Handle Grip

Our ergonomic-design handle grip offers superior comfort and excellent balance for the user.



\*Model shown CER420

#### H.E.R.E Technology

High Efficiency Recirculatory Engine  
A unique MARUYAMA engineered system that is low emission, high power and highly fuel efficient. EU stage 2 compliant.



#### Reverse Start 2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.