

BRUSH CUTTERS



BC2321RS

Specifications

BC2321RS Specifications

Dimensions (LxWxH)	1780x310x355 mm
Dry Weight	5.7kg
Engine	CER230 (22.5cc)
Output	0.77kw
Fuel tank	0.45L
Handle	Loop
Recoil Starting System	Reverse Start 2
Drive Shaft	Solid steel \varnothing 7mm
Accessory (Blade)	4 teeth (230)
Accessory (Nylon head)	Semi-Auto (L)4
Harness	Single
Vibration Level* ¹	
Front Handle(Blade/Nylon)	5.5/6.8m/s ²
Rear Handle(Blade/Nylon Head)	4.8/3.6m/s ²
Sound Pressure Level (Blade/Nylon Head)* ²	91.5/93.5dB(A)

*¹ Vibration Level on the handles measured according to ISO 22867 (m/s²)

*² Sound Pressure Level measured according to ISO 22868

Where ever you are, What ever the job.
Make it a Maruyama Brush cutter.



Treaded Clutch Shaft

The solid steel inner drive-shaft is treaded at the clutch end, which eliminates vibration.



Ergonomic Design Handle Grip
Our ergonomic-design handle grip offers superior comfort and excellent balance for the user.



*Model shown CER420

H.E.R.E Technology

High Efficiency Recirculatory Engine
A unique MARUYAMA engineered system that is low emission, high power and highly fuel efficient. EU stage 2 compliant.



Reverse Start 2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.