

BRUSH CUTTERS



BC3021RS

Specifications

BC3021RS Specifications

Dimensions (LxWxH)	1780x310x335 mm
Dry Weight	5.7kg
Engine	CER300 (30.1cc)
Output	1.0kw
Fuel tank	0.6L
Handle	Loop
Recoil Starting System	Reverse Start 2
Drive Shaft	Solid steel \varnothing 7mm
Accessory (Blade)	3 teeth (255)
Accessory (Nylon head)	Semi-Auto (L)4
Harness	Double
Vibration Level* ¹	
Front Handle(Blade/Nylon)	4.3/7.5m/s ²
Rear Handle(Blade/Nylon Head)	3.4/3.9m/s ²
Sound Pressure Level (Blade/Nylon Head)* ²	95.5/96.5d/B(A)

*¹ Vibration Level on the handles measured according to ISO 22867 (m/s²)

*² Sound Pressure Level measured according to ISO 22868

Where ever you are, What ever the job.
Make it a Maruyama Brush cutter.



Treaded Clutch Shaft

The solid steel inner drive-shaft is threaded at the clutch end, which eliminates vibration.



Ergonomic Design Handle Grip

Our ergonomic-design handle grip offers superior comfort and excellent balance for the user.



*Model shown CER420

H.E.R.E Technology

High Efficiency Recirculatory Engine
A unique MARUYAMA engineered system that is low emission, high power and highly fuel efficient. EU stage 2 compliant.



Reverse Start 2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.