

# BRUSH CUTTERS



## BC4321RS

### Specifications

#### BC4321RS Specifications

Dimensions (LxWxH)	1855x355x365 mm
Dry Weight	8.1kg
Engine	CER420 (41.5cc)
Output	1.57kw
Fuel tank	1.0L
Handle	Loop
Recoil Starting System	Reverse Start 2
Drive Shaft	Solid steel ø8mm
Accessory (Blade)	3 teeth (255)
Accessory (Nylon head)	Semi-Auto (L)5
Harness	Double
Vibration Level* <sup>1</sup>	
Front Handle(Blade/Nylon)	4.7/6.0m/s <sup>2</sup>
Rear Handle(Blade/Nylon Head)	6.3/7.7m/s <sup>2</sup>
Sound Pressure Level (Blade/Nylon Head)* <sup>2</sup>	96.5/98.5dB(A)

\*<sup>1</sup> Vibration Level on the handles measured according to ISO 22867 (m/s<sup>2</sup>)

\*<sup>2</sup> Sound Pressure Level measured according to ISO 22868

Where ever you are, What ever the job.  
Make it a Maruyama Brush cutter.



#### Treaded Clutch Shaft

The solid steel inner drive-shaft is threaded at the clutch end, which eliminates vibration



#### Ergonomic Design Handle Grip

Our ergonomic-design handle grip offers superior comfort and excellent balance for the user.



#### H.E.R.E. Technology

An engine system that is low emission, high power and highly fuel efficient.



#### Reverse Start 2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.