

BRUSH CUTTERS



BCGX25H
BCGX25H
 BCGX25H



Specifications

Where ever you are, What ever the job.
 Make it a Maruyama Brush cutter.

BCGX25H Specifications

| | |
|---|-------------------------|
| Dimensions (LxWxH) | 1795x590x450 mm |
| Dry Weight | 6.0kg |
| Engine | HONDA GX25 (25.0cc) |
| Output | 0.72kw |
| Fuel tank | 0.53L |
| Handle | Double |
| Recoil Starting System | Standard |
| Drive Shaft | Solid steel ø7mm |
| Accessory (Blade) | 4 Teeth (255) |
| Accessory (Nylon head) | Semi-Auto (L)4 |
| Harness | Single |
| Vibration Level* ¹ | |
| Left Handle(Blade/Nylon) | 5.2/5.4m/s ² |
| Right Handle(Blade/Nylon Head) | 4.5/4.7m/s ² |
| Sound Pressure Level (Blade/Nylon Head)* ² | 89.0/91.5dB(A) |

*¹Vibration Level on the handles measured according to ISO 22867 (m/s²)

*² Sound Pressure Level measured according to ISO 22868



Thinking about the Environment

Compared to typical two strokes, the new Honda 4-stroke brushcutters emit significantly less smoke and fumes and less hydrocarbons.



Treaded Clutch Shaft

The solid steel inner drive-shaft is threaded at the clutch end, which eliminates vibration.



DIATOP Bump Feed Z4

DIATOP is a leading innovator in nylon heads, making the Z4 a perfect accessory for your MARUYAMA brush cutter.



Ergonomic Design Handle Grip

Our ergonomic-design handle grip offers superior comfort and excellent balance for the user.