


MULTI-CUTTERS



Specifications

MC2600H-RS Specifications

Dry Weight	4.9 kg
Engine	EE260 (25.4cc)
Output	0.74 kw
Fuel Tank	0.6 L
Handle Type	Double
Drive Shaft	Solid steel $\Phi 7$
Recoil Starting System	Reverse start2
Vibration Level*1	
Front Handle (Blade/Nylon Head)	4.8/4.5 m/s ²
Rear Handle (Blade/Nylon Head)	4.8/4.8 m/s ²
Sound Pressure Level(Blade/Nylon Head)*2	94.5/98.5 dB(A)

*1 Vibration levels on the handles measured according to ISO 22867 m/s² with MC-S (trimmer attachment)

*2 Equivalent Sound Pressure level with MC-S (Blade/Nylon head) ISO22868



Treaded Clutch Shaft

The solid steel inner drive-shaft is threaded at the clutch end, which eliminates vibration.



Ergonomic Design Handle Grip

Our ergonomic-design handle grip offers superior comfort and excellent balance for the user.



Reverse Start 2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.



Snap Lock Joint System

Solid steel, bearing-supported drive shafts feature a split shaft design allowing easy "snap-lock" changeovers to any Maruyama Multi-Cutter attachment.