

## **MD180DX-30 Specifications**

Dimensions(LxWxH)	410/475/720 mm
Dry Weight	11.7 kg
Engine	KAWASAKI TK65 (64.7cc)
Displacement	2.9 kw
Recoil Starter System	Standard
Spark Plug	NGK BPMR7A
Ignition System	C.D.I.
Chemical Tank	30 L
Max. Discharge Volume	3.8L/min
Mist Reach Distance (Horizontal)	14 m
Mist Reach Distance (Verticle)	11 m
Vibration Level (Grip Handle) *1	1.35 m/s <sup>2</sup>
Guaranteed Sound Power Level*2	74.7 dB(A)

- \*1 Vibration level on the throttle handle measured according to ANSI B175.2
- \*2 Guaranteed sound power level EC directive 2000/14/EC, ISO11094

## Powerful blowing performance equiped with KAWASAKI TK65 2 cycle engine.



Turbo Fan Maruyama' s Turbo fan makes for high air capacity with superior efficiency.



**Chemical Reach Distance** Horizontal spray distance of 14 meters. Vertical Spray distance of 10 meters.



Mist Nozzle Assembly Ideal for a wide variety of spraying jobs.



**KAWASAKI TK65** 

This proven "KAWASAKI TK" engine is designed with Kawasaki's new air-head scavenging method, which conforms to exhaust emission regulations in the USA and Europe.

