

BRUSH CUTTERS



BC2621RS

Specifications

BC2621RS Specifications

Dimensions (LxWxH)	1780x310x355 mm
Dry Weight	5.8kg
Engine	CER260 (25.4cc)
Output	0.83kw
Fuel tank	0.6L
Handle	Loop
Recoil Starting System	Reverse Start 2
Drive Shaft	Solid steel \varnothing 7mm
Accessory (Blade)	4 teeth (230)
Accessory (Nylon head)	Semi-Auto (L)4
Harness	Single
Vibration Level* ¹	
Front Handle(Blade/Nylon)	5.3/7.0m/s ²
Rear Handle(Blade/Nylon Head)	4.4/3.7m/s ²
Sound Pressure Level (Blade/Nylon Head)* ²	96.0/97.5dB(A)

*¹ Vibration Level on the handles measured according to ISO 22867 (m/s²)

*² Sound Pressure Level measured according to ISO 22868

Where ever you are, What ever the job.
Make it a Maruyama Brush cutter.



Treaded Clutch Shaft

The solid steel inner drive-shaft is threaded at the clutch end, which eliminates vibration.



Ergonomic Design Handle Grip

Our ergonomic-design handle grip offers superior comfort and excellent balance for the user.



*Model shown CER420

H.E.R.E. Technology

High Efficiency Recirculatory Engine
A unique MARUYAMA engineered system that is low emission, high power and highly fuel efficient. EU stage 2 compliant.



Reverse Start 2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.