



BC3021H-RS Specifications	
Dimensions (LxWxH)	1780x730x465 mm
Dry Weight	6.1kg
Engine	CER300 (30.1cc)
Output	1.0kw
Fuel tank	0.6L
Handle	Double
Recoil Starting System	Reverse Start 2
Drive Shaft	Solid steel ø7mm
Accessory (Blade)	3 teeth (255)
Accessory (Nylon head)	Semi-Auto L(4)
Harness	Double
Vibration Level* 1	
Left Handle(Blade/Nylon)	4.1/5.5m/s ²
Right Handle(Blade/Nylon Head)	5.1/5.8m/s ²
Sound Pressure Level (Blade/Nylon Head)* 2	95.5/96.5dB(A)
*1 Vibration Level on the handles measured according to ISO 22867 (m/s ²)	

^{*1}Vibration Level on the handles measured according to ISO 22867 (m/s²)

Where ever you are, What ever the job. Make it a Maruyama Brush cutter.



Treaded Clutch Shaft
The solid steel inner drive-shaft is
threaded at the clutch end, which
eliminates vibration.



*Model shown CER42

H.E.R.E Technology
High Efficiency Recirculatory Engine
A unique MARUYAMA enginered
system that is low emission,
high power and highly fuel
efficient. EU stage 2 complient.



Ergonomic Design Handle Grip Our ergonomic-design handle grip offers superior comfort and excellent balance for the user.



Reverse Start 2
The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy

starters



 $[\]star^2$ Sound Pressure Level measured according to ISO 22868