


BRUSH CUTTERS



BC500H-RS
BC500H-RS
BC500H-RS



Specifications

BC500H-RS Specifications

Dimensions (LxWxH)	1840x730x480 mm
Dry Weight	8.4kg
Engine	AE500 (50.2cc)
Output	1.47kw
Fuel tank	1.0L
Handle	Double
Recoil Starting System	Reverse Start 2
Drive Shaft	Solid steel $\varnothing 8\text{mm}$
Accessory (Blade)	3 teeth (255)
Accessory (Nylon head)	Semi-Auto (L)5
Harness	Double
Vibration Level* ¹	
Left Handle(Blade/Nylon)	3.8/4.1m/s ²
Right Handle(Blade/Nylon Head)	3.4/3.7m/s ²
Sound Pressure Level (Blade/Nylon Head)* ²	96.0/101.0dB(A)

*¹ Vibration Level on the handles measured according to ISO 22867 (m/s²)

*² Sound Pressure Level measured according to ISO 22868

Where ever you are, What ever the job.
Make it a Maruyama Brush cutter.



Treaded Clutch Shaft

The solid steel inner drive-shaft is threaded at the clutch end, which eliminates vibration



Long Seller

Our precise engineering and quality manufacturing has made this line one of our customer favorites.



DIATOP Bump Feed Z5

DIATOP is a leading innovator in nylon heads, making the Z5 a perfect accessory for your MARUYAMA brush cutter.



Reverse Start 2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.