


BRUSH CUTTERS



BCGX25
BCGX25
BCGX25



Specifications

BCGX25 Specifications

Dimensions (LxWxH)	1795x310x360 mm
Dry Weight	5.7kg
Engine	HONDA GX25 (25.0cc)
Output	0.72kw
Fuel tank	0.53L
Handle	Loop
Recoil Starting System	Standard
Drive Shaft	Solid steel \varnothing 7mm
Accessory (Blade)	4 Teeth (255)
Accessory (Nylon head)	Semi-Auto Head (L)4
Harness	Single
Vibration Level* ¹	
Front Handle(Blade/Nylon)	5.6/5.0m/s ²
Rear Handle(Blade/Nylon Head)	7.5/7.0m/s ²
Sound Pressure Level (Blade/Nylon Head)* ²	89.0/91.5dB(A)

*¹Vibration Level on the handles measured according to ISO 22867 (m/s²)

*²Sound Pressure Level measured according to ISO 22868

Where ever you are, What ever the job.
Make it a Maruyama Brush cutter.



Thinking about the Environment
Compared to typical two strokes, the new Honda 4-stroke brushcutters emit significantly less smoke and fumes and less hydrocarbons.



Treaded Clutch Shaft
The solid steel inner drive-shaft is threaded at the clutch end, which eliminates vibration.



DIATOP Bump Feed Z4
DIATOP is a leading innovator in nylon heads, making the Z4 a perfect accessory for your MARUYAMA brush cutter.



Ergonomic Design Handle Grip
Our ergonomic-design handle grip offers superior comfort and excellent balance for the user.