


# HEDGE TRIMMERS



HT230D  
HT230D  
HT230D



## Specifications

### HT230D Specifications

Dimensions (LxWxH)	1025x245x220mm
Dry weight	5.1kg
Engine	LE230 (22.5cc)
Output	0.58kw
Fuel tank	0.5L
Blade Type	Double
Blade Length	750mm
Blade Thickness	2.5mm
Recoil Starting System	Standard
Handle Type	Fixed
Vibration level* <sup>1</sup>	
Rear handle	9.0m/s <sup>2</sup>
Front handle	11.0m/s <sup>2</sup>
Sound power level Guaranteed* <sup>2</sup>	106dB(A)

\*<sup>1</sup> Vibration Level on the handles measured according to ISO 5349 (m/s<sup>2</sup>)

\*<sup>2</sup> Sound Power Level guaranteed according to 2000/14/EC and measured according to ISO3744, ISO11094

Trimming has never been easier with Maruyama's extensive range of Hedge trimmers.



#### Blade Speed

When it comes to blade speed, MARUYAMA hedge trimmers are extremely fast. Giving a cleaner cut each and everytime.




#### Resistent to Deflection

MARUYAMA's blades and guide bars are extremely thick, minimizing bending and bowing, we improve the cut and make operation easier.



#### Durable Gearcase

Long life usability due to MARUYAMA's higher quality materials and components.



#### 3 Cutting Surface Blade

The induction hardened chrome steel blades are polish ground sharpened on all three cutting surfaces for a cleaner cut.