



## **HT230DL-R Specifications Dimensions (LxWxH)** 1175x245x225mm 5.4kg Dry weight LE230 22.5cc **Engine** 0.58kw **Output Fuel tank** 0.5L **Blade Type** Double **Blade Length** 750mm **Blade Thickness** 2,5mm Standard **Recoil Starting System** Rotational Handle type Vibration level\* 1 8.0m/s<sup>2</sup> Rear handle 12.0m/s<sup>2</sup> Front handle Sound power level Guaranteed\*<sup>2</sup> 106dB(A)

Trimming has never been easier with Maruyama's extensive range of Hedge trimmers.



**Blade Speed**When it comes to blade speed, MARUYAMA hedge trimmers are extremly fast.
Giving a cleaner cut each and everytime.



**Durable Gearcase**Long life usabilty due to MARUYAMA's higher quality materials and components.



**5 Position Rotational Handle**The handle can be positioned every
45 degrees giving the operator
excellent cutting flexibility.



**3 Cutting Surface Blade**The induction hardened chrome steel blades are polish ground sharpened on all three cutting surfaces for a cleaner cut.



 $st^{1}$  Vibration Level on the handles measured according to ISO 5349 (m/s )

 $<sup>*^2</sup>$  Sound Power Level guaranteed according to 2000/14/  $\to$  C and measured according to ISO3744 $\setminus$  ISO11094