


HEDGE TRIMMERS



NEW
Reverse Start
MARUYAMA
REVERSE Start

HT230DLS
HT230DLS-R
HT230DLS-R



Specifications


HT230DLS-R Specifications

Dimensions (LxWxH)	1170x245x230mm
Dry weight	5.5kg
Engine	LE230 (22.5cc)
Output	0.58kw
Fuel tank	0.5L
Blade Type	Double
Blade Length	750mm
Blade Thickness	2.5mm
Recoil Starting System	Reverse Start 2
Handle type	Rotational
Vibration level* ¹	
Rear handle	8.0m/s ²
Front handle	12.0m/s ²
Sound power level Guaranteed* ²	106dB(A)

*¹ Vibration Level on the handles measured according to ISO 5349 (m/s²)

*² Sound Power Level guaranteed according to 2000/14/EC and measured according to ISO3744, ISO11094

Trimming has never been easier with Maruyama's extensive range of Hedge trimmers.



Blade Speed

When it comes to blade speed, MARUYAMA hedge trimmers are extremely fast. Giving a cleaner cut each and everytime.




5 Position Rotational Handle

The handle can be positioned every 45 degrees giving the operator excellent cutting flexibility.



Reverse Start 2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.



3 Cutting Surface Blade

The induction hardened chrome steel blades are polish ground sharpened on all three cutting surfaces for a cleaner cut.