


HEDGE TRIMMERS



NEW
Reverse Start

HT230DS
HT230DS-R
HT230DS-R



Specifications

HT230DS-R Specifications

Dimensions (LxWxH)	1035x245x230mm
Dry weight	5.3kg
Engine	LE230 (22.5cc)
Output	0.58kw
Fuel tank	0.5L
Blade Type	Double
Blade Length	600mm
Blade Thickness	2.5mm
Recoil Starting System	Reverse Start 2
Handle type	Rotational
Vibration level* ¹	
Rear handle	11.0m/s ²
Front handle	14.0m/s ²
Sound power level Guaranteed* ²	106dB(A)

*¹ Vibration Level on the handles measured according to ISO 5349 (m/s²)

*² Sound Power Level guaranteed according to 2000/14/EC and measured according to ISO3744, ISO11094

Trimming has never been easier with Maruyama's extensive range of Hedge trimmers.




Durable Gearcase

Long life usability due to MARUYAMA's higher quality materials and components.



Reverse Start 2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.



3 Cutting Surface Blade

The induction hardened chrome steel blades are polish ground sharpened on all three cutting surfaces for a cleaner cut.



5 Position Rotational Handle

The handle can be positioned every 45 degrees giving the operator excellent cutting flexibility.