


# HEDGE TRIMMERS

**NEW**  
**Reverse Start**  
 MARUYAMA  
 REVERSE<sup>2</sup>  
 start



HT230PS  
 HT230PS  
 HT230PS



## Specifications

Trimming has never been easier with Maruyama's extensive range of Hedge trimmers.

### HT230PS Specifications

|  |                      |
|--|----------------------|
| Dimensions (LxWxH)                         | 1045x270x260mm       |
| Dry weight                                 | 5.4kg                |
| Engine                                     | LE230 (22.5cc)       |
| Output                                     | 0.58kw               |
| Fuel tank                                  | 0.5L                 |
| Blade Type                                 | Single               |
| Blade Length                               | 750mm                |
| Blade Thickness                            | 2.5mm                |
| Recoil Starting System                     | Reverse Start2       |
| Handle type                                | Fixed                |
| Vibration level* <sup>1</sup>              |                      |
| Rear handle                                | 10.0m/s <sup>2</sup> |
| Front handle                               | 9.0m/s <sup>2</sup>  |
| Sound power level Guaranteed* <sup>2</sup> | 107dB(A)             |

\*<sup>1</sup> Vibration Level on the handles measured according to ISO 5349 (m/s )

\*<sup>2</sup> Sound Power Level guaranteed according to 2000/14/ E C and measured according to ISO3744, ISO11094



#### Blade Plate

Sturdy aluminium plate that collects leaves and debris while you cut.




#### Single Blade

Induction hardened chrome steel single blade is 750mm long, giving excellent reach and lifetime durability.



#### Durable Gearcase

Long life usability due to MARUYAMA's higher quality materials and components.



#### 3 Cutting Surface Blade

The induction hardened chrome steel blades are polish ground sharpened on all three cutting surfaces for a cleaner cut.