


HEDGE TRIMMERS



HT2350DS-RX
HT2350DS-RX



Specifications

HT2350DS-RX Specifications	
Dimensions (LxWxH)	1015x240x214mm
Dry weight	4.6kg
Engine	HE230 (22.5cc)
Output	0.58kw
Fuel tank	0.4L
Blade Type	Double
Blade Length	600mm
Blade Thickness	2.3mm
Recoil Starting System	Reverse Start 2
Handle type	Rotational
Vibration level* ¹	
Rear handle	10.0m/s ²
Front handle	11.0m/s ²
Sound power level Guaranteed* ²	108dB(A)

*¹ Vibration Level on the handles measured according to ISO 5349 (m/s²)

*² Sound Power Level guaranteed according to 2000/14/ E.C and measured according to ISO3744, ISO11094

Trimming has never been easier with Maruyama's extensive range of Hedge trimmers.




5 Position Rotational Handle

The handle can be positioned every 45 degrees giving the operator excellent cutting flexibility.



Resistant to Deflection

MARUYAMA's blades and guide bars are extremely thick, minimizing bending and bowing, we improve the cut and make operation easier.



Blade Speed

When it comes to blade speed, MARUYAMA hedge trimmers are extremely fast. Giving a cleaner cut each and everytime.



Reverse Start2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.