


HEDGE TRIMMERS



HT236DLSV-R
HT236DLSV-R
 HT236DLSV-R



Specifications


Trimming has never been easier with Maruyama's extensive range of Hedge trimmers.

HT236DLSV-R Specifications

Dimensions (LxWxH)	1170x240x215mm
Dry weight	5.4kg
Engine	HE230 (22.5cc)
Output	0.58kw
Fuel tank	0.4L
Blade Type	Double
Blade Length	750mm
Blade Thickness	2.3mm
Recoil Starting System	Reverse Start 2
Handle type	Rotational
Vibration level* ¹	
Rear handle	7.0m/s ²
Front handle	4.0m/s ²
Sound power level Guaranteed* ²	108dB(A)

*¹ Vibration Level on the handles measured according to ISO 5349 (m/s²)

*² Sound Power Level guaranteed according to 2000/14/EC and measured according to ISO3744, ISO11094



Hybrid Anti-Vibration System
 Using both spring and rubber dampers to reduce vibration and operator fatigue



Reverse Start 2
 The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.



3 Cutting Surface Blade
 The induction hardened chrome steel blades are polish ground sharpened on all three cutting surfaces for a cleaner cut.



5 Position Rotational Handle
 The handle can be positioned every 45 degrees giving the operator excellent cutting flexibility.