


HEDGE TRIMMERS



HT236DLV-R
HT236DLV-R
HT236DLV-R



Specifications


HT236DLV-R Specifications

Dimensions (LxWxH)	1170x240x215mm
Dry weight	5.4kg
Engine	HE230 (22.5cc)
Output	0.58kw
Fuel tank	0.4L
Blade Type	Double
Blade Length	750mm
Blade Thickness	2.3mm
Recoil Starting System	Standard
Handle type	Rotational
Vibration level* ¹	
Rear handle	7.0m/s ²
Front handle	4.0m/s ²
Sound power level Guaranteed* ²	108dB(A)

*¹ Vibration Level on the handles measured according to ISO 5349 (m/s²)

*² Sound Power Level guaranteed according to 2000/14/EC and measured according to ISO3744, ISO11094


Trimming has never been easier with Maruyama's extensive range of Hedge trimmers.



Hybrid Anti-Vibration System
Using both spring and rubber dampers to reduce vibration and operator fatigue



Blade Speed
When it comes to blade speed, MARUYAMA hedge trimmers are extremely fast. Giving a cleaner cut each and everytime.



3 Cutting Surface Blade
The induction hardened chrome steel blades are polish ground sharpened on all three cutting surfaces for a cleaner cut.



5 Position Rotational Handle
The handle can be positioned every 45 degrees giving the operator excellent cutting flexibility.