


HEDGE TRIMMERS



HT236DS
HT236DSV-R
HT236DSV-R



Specifications


Trimming has never been easier with Maruyama's extensive range of Hedge trimmers.

HT236DSV-R Specifications

Dimensions (LxWxH)	1030x240x215mm
Dry weight	5.2kg
Engine	HE230 (22.5cc)
Output	0.58kw
Fuel tank	0.4L
Blade Type	Double
Blade Length	600mm
Blade Thickness	2.3mm
Recoil Starting System	Reverse Start 2
Handle type	Rotational
Vibration level* ¹	
Rear handle	7.0m/s ²
Front handle	4.0m/s ²
Sound power level Guaranteed* ²	108dB(A)

*¹ Vibration Level on the handles measured according to ISO 5349 (m/s²)


*² Sound Power Level guaranteed according to 2000/14/EC and measured according to ISO3744, ISO11094



Hybrid Anti-Vibration System
Using both spring and rubber dampers to reduce vibration and operator fatigue



Blade Speed
When it comes to blade speed, MARUYAMA hedge trimmers are extremely fast. Giving a cleaner cut each and everytime.



3 Cutting Surface Blade
The induction hardened chrome steel blades are polish ground sharpened on all three cutting surfaces for a cleaner cut.



5 Position Rotational Handle
The handle can be positioned every 45 degrees giving the operator excellent cutting flexibility.