

# MULTI-CUTTERS



## MC2600RS



## Specifications

### MC2600RS Specifications

Dimensions(LxWxH)	1025x320x225 mm
Dry Weight	4.7 kg
Engine	EE260 (25.4cc)
Output	0.74 kw
Fuel Tank	0.6 L
Handle Type	Loop
Drive Shaft	Solid steel $\Phi 7$
Recoil Starting System	Reverse start2
Vibration Level*1	
Front Handle (Blade/Nylon Head)	6.8/5.5 m/s <sup>2</sup>
Rear Handle (Blade/Nylon Head)	6.8/7.5 m/s <sup>2</sup>
Sound Pressure Level(Blade/Nylon Head)*2	94.5/98.5 dB(A)

\*1 Vibration levels on the handles measured according to ISO 22867 m/s<sup>2</sup> with MC-S (trimmer attachment)

\*2 Equivalent Sound Pressure level with MC-S (Blade/Nylon head) ISO22868



#### Treaded Clutch Shaft

The solid steel inner drive-shaft is threaded at the clutch end, which eliminates vibration.



#### Ergonomic Design Handle Grip

Our ergonomic-design handle grip offers superior comfort and excellent balance for the user.



#### Reverse Start 2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.



#### Snap Lock Joint System

Solid steel, bearing-supported drive shafts feature a split shaft design allowing easy "snap-lock" changeovers to any Maruyama Multi-Cutter attachment.



# MARUYAMA