


MULTI-CUTTERS



MC2621RS



Specifications

MC2621RS Specifications

Dimensions(LxWxH)	1035x320x230 mm
Dry Weight	4.5 kg
Engine	CER260 (25.4cc)
Output	0.81 kw
Fuel Tank	0.6 L
Handle Type	Loop
Drive Shaft	Solid steel $\Phi 7$
Recoil Starting System	Reverse start2
Vibration Level*1	
Front Handle (Blade/Nylon Head)	6.8/5.5 m/s ²
Rear Handle (Blade/Nylon Head)	6.8/7.5 m/s ²
Sound Pressure Level(Blade/Nylon Head)*2	96.0/97.5 dB(A)

*1 Vibration levels on the handles measured according to ISO 22867 m/s² with MC-S (trimmer attachment)

*2 Equivalent Sound Pressure level with MC-S (Blade/Nylon head) ISO22868



Treaded Clutch Shaft

The solid steel inner drive-shaft is threaded at the clutch end, which eliminates vibration.



Ergonomic Design Handle Grip

Our ergonomic-design handle grip offers superior comfort and excellent balance for the user.



H.E.R.E. Technology

High Efficiency Recirculatory Engine
A unique MARUYAMA engineered system that is low emission, high power and highly fuel efficient. EU stage 2 compliant.

*Model shown CER420



Reverse Start 2

The Reverse Start 2 system has incorporated the best features of an electric starter, fast and easy starters.



MARUYAMA